

# 5B-L-S-C-BANDVVV-XXXX-X ANTENNA FAMILY

# 5 Inch Blade Antenna for Video / Data Link

The 5B-L-S-C-BandVVV-XXXX-X is triple-band blade antenna for video and data link applications. The rugged enclosure is designed to survive ground and flight environments.

The antenna includes separate connectors for the L, S and C-Band frequency ranges. Each port is optimized for minimal return loss ensuring efficient transmission and reception of RF signals.



#### **BENEFITS**

- Minimize weight and aerodynamic drag with this combo antenna
- Good impedance match for efficient antenna performance

### **FEATURES**

- L, S and C-Band coverage in a single antenna enclosure
- Connector type customizable for each frequency band
- · Vertically polarized, omni directional coverage
- · High power handling

#### **OPTIONS**

COLOR • Gloss White

Lusterless GrayCamo Green

Lusterless Black

Desert Tan

CONNECTOR

TNC

SMA

Type N

#### **ELECTRICAL**

Frequency Range	
L-Band	1700-2000 MHz
S-Band	2200-2500 MHz
C-Band	4400-6000 MHz
VSWR	
L-Band	< 2.0:1
S-Band	< 2.0:1
C-Band	< 2.5:1
Impedance	50 ohms


#### **MECHANICAL & ENVIRONMENTAL**


Designed to:


Weight	5.4 oz Typical
Temperature	-55°C TO +85°C
Altitude	70,000 ft
Vibration	> 30 Grms

### **LIMITING & FILTERING**

Power Handling	50 Watt CW
I	







## PART NUMBER DECODER



## **CONTACT ANTCOM**

Phone: +1-310-782-1076 Fax: +1-310-782-1086 Email: sales.pi.antcom@antcom.com Web: antcom.com

