



CPT7700

Compact enclosure with SPAN
GNSS+INS technology from
Hexagon | NovAtel delivers 3D
position, velocity and attitude

World-leading GNSS+INS technology

SPAN GNSS+INS technology brings together two different but complementary technologies: Global Navigation Satellite System (GNSS) positioning and Inertial Navigation System (INS). The absolute accuracy of GNSS positioning with the stability of inertial measurement unit (IMU) gyro and accelerometer measurements generate a 3D navigation solution that is stable and continuously available. Deeply coupling the GNSS and inertial measurements through SPAN technology enables better bridging through GNSS interruptions and rapid reacquisition of signals.

CPT7700 overview

The CPT7700 is a compact, single enclosure GNSS+INS receiver powered by world-class OEM7 technology from NovAtel. Capable of delivering up to centimetre-level accuracy, customers can choose from a variety of positioning modes to ensure they have the optimal level of accuracy for their application.

The CPT7700 contains a high performing and highly reliable Honeywell HG4930 Micro Electromechanical System (MEMS) IMU to deliver leading-edge SPAN technology from NovAtel in an integrated, single enclosure solution. It provides tactical grade performance for unmanned vehicles, mobile mapping and other commercial and/or military guidance applications. The CPT7700 is a small, lightweight and low-power solution with multiple communication interfaces for easy integration on multiple platforms.

CPT7700 advantages

The deep coupling of the GNSS and IMU measurements delivers the most satellite observations and the most accurate, continuous solution possible. Further, the CPT7700 is comprised entirely of commercial components, simplifying export restrictions involved with traditional GNSS+INS systems.

Improve CPT7700 accuracy

CPT7700 provides your choice of accuracy and performance, from decimetre to RTK-level positioning. For more demanding applications, Inertial Explorer post-processing software can be used to post-process the real-time SPAN GNSS+INS solution to provide the system's highest level of accuracy.



Benefits

- High-performance SPAN GNSS+INS solution with configurable application profiles
- Small, low-power, all-in-one GNSS+INS enclosure
- Easy integration into space and weight constrained applications
- Commercially exportable system
- Rugged design ideal for challenging environments
- Enhanced connection options including serial, USB, CAN and Ethernet
- Future-proof for upcoming GNSS signal support

Features

- MEMS gyros and accelerometers
- Small size, rugged and lightweight
- Dedicated wheel sensor input
- TerraStar Correction Services supported over multi-channel L-Band and IP connections
- Spoofing detection, interference detection and mitigation provided by GNSS Resilience and Integrity Technology (GRIT)
- Supports Precision Time Protocol (PTP)
- 16 GB of internal storage
- Four receiver status LEDs

SPAN system performance¹

Signal tracking

GPS	L1 C/A, L1C, L2C, L2P, L5
GLONASS ²	L1 C/A, L2 C/A, L2P, L3, L5
Galileo ³	E1, E5 AltBOC, E5a, E5b, E6
BeiDou	B1I, B1C, B2I, B2a, B2b, B3
QZSS	L1 C/A, L1C, L1S, L2C, L5, L6
NavIC (IRNSS)	L5
SBAS	L1, L5
L-Band	up to 5 channels

Horizontal position accuracy (RMS)

Single point L1/L2	1.2 m
SBAS ⁴	60 cm
TerraStar-L ⁵	40 cm
TerraStar-C PRO ⁵	2.5 cm
TerraStar-X ⁵	2.0 cm
RTK	1 cm + 1 ppm

Heave performance

Instantaneous	5 cm or 5%
Delayed	3.5 cm or 3.5%
Post-processed (Inertial Explorer)	2.5 cm or 2.5%

Maximum data rate

GNSS measurements	up to 20 Hz
GNSS position	up to 20 Hz
INS solution	up to 200 Hz
IMU raw data rate	100 Hz or 400 Hz

Time to first fix⁶

Cold start	< 34 s (typ)
Hot start	< 20 s (typ)

Signal reacquisition

L1	< 0.5 s (typ)
L2/L5	< 1.0 s (typ)

Time accuracy⁷

< 5 ns RMS

Velocity accuracy

< 0.03 m/s RMS

Velocity limit⁸

600 m/s

IMU performance⁹

Gyroscope performance

Technology	MEMS
Dynamic range ¹⁰	400 °/s
Bias instability	0.45 °/hr
Angular random walk	0.06 °/√hr

Accelerometer performance

Technology	MEMS
Dynamic range	20 g
Bias instability	0.075 mg
Velocity random walk	0.06 m/s/√hr

Environmental

Temperature

Operating	-40°C to +71°C
Storage	-40°C to +85°C

Humidity	95% non-condensing
----------	--------------------

Submersion	2 m for 12 hours (IEC 60529 IP68)
------------	-----------------------------------

Water	MIL-STD-810H, Method 512.6
-------	----------------------------

Dust	MIL-STD-810H, Method 510.7
------	----------------------------

Vibration (operating)

Random	MIL-STD-810H, Method 514.8, Category 24, 7.7 g RMS
Sinusoidal	IEC 60068-2-6

Acceleration (operating)	MIL-STD-810H, Method 513.8, Procedure II (G Loading - 15 g)
--------------------------	---

Bump (operating)	IEC 60068-2-27 Ea (25 g)
------------------	--------------------------

Shock (operating)	MIL-STD-810H, Method 516.8, Procedure 1, 40 g, 11 ms terminal sawtooth
-------------------	--

Physical and electrical

Dimensions ¹¹	90 x 60 x 60 mm
--------------------------	-----------------

Weight	500 g
--------	-------

Power

Power consumption ¹²	9 W (typ)
Input voltage	+9 to +32 VDC

Antenna LNA power output

Output voltage	5 VDC ±5%
Maximum current	200 mA

Input/Output connectors

Antenna	1 x SMA
Power and I/O	2 x Fischer Core
	16 pin DPBU 104 A086 140G/240G

Communication ports

1 RS-422	up to 460,800 bps
1 RS-232	up to 460,800 bps
1 USB device	HS
1 Ethernet	10/100 Mbps
1 CAN Bus	1 Mbps
3 Event input	
3 Event output	
1 Wheel sensor input	

Status LEDs

Power, Position, INS, Logging

Compliance

FCC, ISED, CE and Global Type Approvals ¹³

Optional accessories

- Power and I/O cable
- Mounting Plate

Performance during GNSS outages^{14, 15, 16}

Outage duration	Positioning mode	Position accuracy (m) RMS		Velocity accuracy (m/s) RMS		Attitude accuracy (degrees) RMS	
		Horizontal	Vertical	Horizontal	Vertical	Roll/Pitch	Heading
0 s	RTK ¹⁷	0.02	0.03				
	TerraStar-C PRO PPP	0.025	0.05	0.015	0.010	0.010	0.030
	Single point	1.00	0.60				
10 s	RTK ¹⁷	0.12	0.08				
	TerraStar-C PRO PPP	0.12	0.10	0.035	0.020	0.018	0.040
	Single point	1.10	0.65				
60 s	RTK ¹⁷	3.80	0.73				
	TerraStar-C PRO PPP	3.80	0.75	0.165	0.030	0.030	0.055
	Single point	4.80	1.30				
	RTK with Land profile and DMI	2.50	0.55	0.115	0.030	0.030	0.055
0 s	Post-Processed using Inertial Explorer	0.01	0.02	0.015	0.010	0.003	0.010
10 s		0.01	0.02	0.015	0.010	0.003	0.010
60 s		0.11	0.05	0.017	0.010	0.004	0.014

1. Typical values under ideal, open sky conditions.

2. Hardware ready for L5.

3. E1bc and E6bc support only.

4. GPS-only.

5. Requires subscription to TerraStar correction service.

6. Cold start: no almanac or ephemerides and no approximate position or time.

Hot start: almanac and recent ephemerides saved and approximate position and time entered.

7. Time accuracy does not include biases due to RF or antenna delay.

8. Export licensing restricts operation to a maximum of 600 m/s, message output impacted above 585 m/s.

9. Supplied by IMU manufacturer.

10. Full performance to 325 °/s.

11. Dimensions do not include mounting feet.

12. Typical values using serial port communication without interference mitigation. See manual for power supply considerations.

13. Pending.

14. Performance may be impacted in conditions with unmitigated vibration or significant temperature variations. May vary from part to part.

15. Performance with one antenna, no DMI, and no SPAN profile unless otherwise specified.

16. Typical. Based on mixed urban road vehicle dynamics and benign GNSS conditions.

17. 1 ppm should be added to all position values to account for additional error due to baseline length.

Contact Hexagon | NovAtel

sales.nov.ap@hexagon.com 1-800-NOVATEL (U.S. and Canada) or 403-295-4900 | China: 0086-21-68882300 | Europe: 44-1993-848-736 | SE Asia and Australia: 61-400-883-601. For the most recent details of this product: novatel.com

This document and the information contained herein are provided AS IS and without any representation or warranty of any kind. All warranties, express or implied, are hereby disclaimed, including but not limited to any warranties of merchantability, non-infringement, and fitness for a particular purpose. Nothing herein constitutes a binding obligation. The information contained herein is subject to change without notice.

Inertial Explorer, NovAtel, OEM7, SPAN and TerraStar are trademarks of Hexagon AB and/or its subsidiaries and affiliates, and/or their licensors. All other trademarks are properties of their respective owners.

© Copyright 2020 – 2023 Hexagon AB and/or its subsidiaries and affiliates. All rights reserved. A list of entities within the Hexagon Autonomy & Positioning division is available at <https://hexagon.com/company/divisions/autonomy-and-positioning>.