

# GAJT-710ML

## Enhanced single enclosure GPS Anti-Jam Technology (GAJT) for land applications

### Jamming and interference are constant threats

Jamming and interference, whether intentional or unintentional, can seriously degrade GNSS position, navigation and timing (PNT) availability—even to the point of total solution denial. Jammers create excessive noise, overpowering the low power GNSS signals and saturating the electronics in a GNSS receiver front end. Methods are needed to suppress this interference so your GNSS receiver continues to operate.

### Enhanced functionality, same battle-proven small form factor

The GAJT-710ML is the next evolution of battle-proven anti-jam technology for land platforms from Hexagon | NovAtel. It offers direction-finding functionality to support enhanced situational awareness and a new silent mode feature that reduces the thermal signature. It also has enhanced GNSS tracking performance. All these improvements are achieved while maintaining the same form and fit of the previous generation product.

### How it works

GAJT-710ML mitigates interference by creating nulls in the antenna gain pattern in the direction of jammers, providing significant anti-jam protection even in dynamic multi-jammer scenarios. The output is a protected standard Radio Frequency (RF) signal, free from jamming and suitable for input to modern and legacy GNSS receivers.

### Leading-edge technology

The commercial off-the-shelf (COTS) system uses NovAtel's seven element antenna array to receive GNSS signals in the L1 and L2 bands. Interference mitigation is achieved by applying proprietary digital null forming algorithms to the signals, creating dynamic nulls to give protection against narrowband and broadband interference sources. The unit is comprised of Radio Frequency (RF) front ends and null forming electronics. Integration to your GNSS receiver is seamless; DC power supply and data output are via separate connectors for which optional cables can be provided.

### Protects GNSS navigation and precise timing receivers

GAJT-710ML protects GPS L1/L2, QZSS L1/L2, SBAS L1 and Galileo E1 signals. The wide bandwidth of the GAJT ensures future compatibility with M-Code GPS.



### Benefits

- Commercial off-the-shelf (COTS)
- Low cost anti-jam protection for land vehicles
- Easy to integrate, ideal for retrofitting
- Anti-jam protection in dynamic multi-jammer scenarios
- Compatible with legacy and modern GNSS receivers, including M-Code
- Provides situational awareness
- Reduced thermal signature

### Features

- Affordable protection for GNSS position, velocity and time
- Up to 55 dB of interference suppression
- Single enclosure system
- Simultaneous GPS L1/L2, QZSS L1/L2, SBAS L1 and Galileo E1 protection
- Supports M-Code on GPS L1 & L2
- Adaptive digital nulling
- Jammer direction-finding
- Silent mode capability

## Performance

### GNSS Signals

**L1 Band** 1575.42 MHz  $\pm$ 12 MHz  
GPS L1, Galileo E1, QZSS L1, SBAS L1

**L2 Band** 1227.6 MHz  $\pm$ 12 MHz  
GPS L2, QZSS L2

### Interference Rejection

#### Simultaneous L1/E1 and L2

Interference suppression 40 dB (typical)  
55 dB (max)

Number of simultaneous nulling directions 6

### Capabilities

- Jammer direction-finding (Situational Awareness)
- Silent mode (for reduced thermal signature)

### Controlled Reception Pattern Antenna (CRPA)

Number of elements 7  
Noise figure (typical) 3 dB  
LNA gain 30 dB  
VSWR  $\leq$ 2.0:1  
RF output 50  $\Omega$  TNC

### Connectors

Power MIL-C-26482, Series 2  
RF TNC (Female)  
Data MIL-DTL-38999, Series 3

## Physical and Electrical

### Dimensions

289 mm diameter  $\times$  120 height mm

**Weight** 7.5 kg

### Power

Power consumption 25 W  
Input voltage +10 to +33 VDC

## Environmental

### Temperature

MIL-STD-810G(CH1) 501.6  
Operating -40°C to +71°C  
Storage -55°C to +85°C

**Humidity** MIL-STD-810G(CH1), 507.6, Proc. II

**Altitude** MIL-STD-810G(CH1), 500.6  
Operating 3,600 m/12,000'  
Storage 12,000 m/40,000'

**Solar Radiation** MIL-STD-810G(CH1), 505.6

**Corrosion** MIL-STD-810G(CH1), 509.6  
MIL-STD-810G(CH1), 518.2  
MIL-STD-810G(CH1), 504.2

**Water** MIL-STD-810G(CH1), 512.6  
MIL-STD-810G(CH1), 506.6  
IEC 60529 IPX6  
IEC 60529 IPX7

**Sand and Dust** MIL-STD-810G(CH1), 510.6  
IEC 60529 IP6X

**Vibration** MIL-STD-810G(CH1), 514.7  
tracked and ground wheeled

**Shock** MIL-STD-810G(CH1), 516.7

**Drop** IEC 60068-2-31 Ec, Proc 1, 50 cm

### Compliance

FCC, ISED, CE, UKCA

### Accessories

- 5 m unterminated GAJT-710 vehicle power cable (01018776)
- GAJT-710 data cable (01019845)

### Export Approvals

Canadian Controlled Goods

## Other GAJT Products

### GAJT-710MS



- Single enclosure system for warships and other marine vessels
- 7-element antenna array
- Easy to integrate, ideal for retrofitting

### GAJT-410ML



- Compact enclosure system for land and fixed applications
- 4-element antenna array
- Direction-finding and jammer status
- Available in Olive Drab or Desert Tan
- Also available in white (GAJT-410MS)

### GAJT-AE-N



- Suitable for smaller platforms including UAVs
- Antenna electronics for 4-element antenna array
- Works with most 4-element antenna arrays (supplied separately)
- Available as a card-only variant (GAJT-AE-R) for space constrained platforms.

### 4-Element Antenna Array

A 4-element antenna array allows gain pattern shapes to be changed in response to interference. Provides 3 independent nulls.



## Contact Hexagon | NovAtel

sales.nov.ap@hexagon.com 1-800-NOVATEL (U.S. and Canada) or 403-295-4900 | China: 0086-21-68882300 | Europe: 44-1993-848-736 | SE Asia and Australia: 61-400-883-601. For the most recent details of this product: novatel.com

*This document and the information contained herein are provided AS IS and without any representation or warranty of any kind. All warranties, express or implied, are hereby disclaimed, including but not limited to any warranties of merchantability, non-infringement, and fitness for a particular purpose. Nothing herein constitutes a binding obligation. The information contained herein is subject to change without notice.*

GAJT and NovAtel are trademarks of Hexagon AB and/or its subsidiaries and affiliates, and/or their licensors. All other trademarks are properties of their respective owners.

© Copyright 2021 – 2023 Hexagon AB and/or its subsidiaries and affiliates. All rights reserved. A list of entities within the Hexagon Autonomy & Positioning division is available at <https://hexagon.com/company/divisions/autonomy-and-positioning>.