

GNSS-502

High-performance antenna for terrestrial applications

Patented technology

The VEXXIS GNSS-500 series antennas provide outstanding circularly polarized, symmetric radiation patterns with superior multipath rejection performance. This is achieved with a patented, multi-point feeding network which provides uniquely low loss and frequency independent amplitude/phase balance. Strictly balancing signals and sequentially feeding the GNSS antenna at multiple points is the key to achieving remarkable performance.

Optimised for terrestrial applications

The GNSS-502 antenna is designed with a low profile, aerodynamic enclosure, ideal for ground vehicles in applications such as agriculture, machine control and mobile mapping. Magnetic mounts make the antenna easy to install or move between ground vehicle platforms. The combination of intelligent enclosure design along with multi-constellation and L-Band support makes it ideal for any terrestrial application.

Ruggedized for challenging environments

The GNSS-502 has been thoroughly tested to withstand even the most challenging environments. It endured over 1000 hours of intense vibration testing to earn its MIL-STD-810G rating. It is also water resistant under heavy rainfall or high pressure spray, ensuring its long survivability under the toughest operating conditions.



Features

- Supports dual-frequency GPS, GLONASS, Galileo, BeiDou and SBAS signal reception
- L-Band signal reception, supporting correction services such as TerraStar
- Multi-point antenna feed provides stable phase center and enhanced multipath rejection
- Designed for high quality performance when used with STEADYLINE technology from Hexagon | NovAtel
- Low-profile design ideal for machine control applications

Performance**Signal Received**

GPS	L1, L2
GLONASS	L1, L2
Galileo	E1, E5b
BeiDou	B1, B2
L-Band	

Pass Band (typical)

Upper passband	1578.0 ± 33.0 MHz
Lower passband	1220.0 ± 31.0 MHz

Out-of-Band Rejection (typical)

Band edges ± 50 MHz	15 dB
Band edges ± 100 MHz	25 dB

LNA Gain (typical)

L1	34 dB
L2	38 dB

Gain at Zenith (90°)

L1/B1/E1/G1/L-Band	+4.0 dBic (minimum)
L2/B2/E5b/G2	+3.5 dBic (minimum)

Gain Roll-Off (Zenith to Horizon)

Upper passband	12 dB (typical)
Lower passband	13 dB (typical)
L-Band	12 dB (typical)

Phase Center Stability <5.0 mm

Noise Figure 2.5 dB (typical)

VSWR ≤2.0 (typical)

L1-L2 Differential Propagation Delay

7 ns (maximum)

Group Delay Ripple <15 ns

Nominal Impedance 50 Ω

Physical and Electrical

Dimensions 155 mm D × 45 mm H

Weight 450 g

Connector TNC female

Mounting 2 × magnetic mounts
2 × M4 screw inserts

Power
Input voltage +3.3 to +18.0 VDC
Current 20 mA (typical)

Environmental**Temperature**

Operating -40°C to +85°C

Storage -55°C to +85°C

Humidity 95% non-condensing

Salt Fog MIL-STD-810G (CH1), 509.6

Water/Dust Resistance IP67, IP69K

Vibration (operating)

Random MIL-STD-810G (CH1), 514.7 (15 g)
Annex E, Procedure 1, Category 24

Shock MIL-STD-810G (CH1), 516.7 (40 g)
Procedure 1

Bump IEC 60068-2-27 Ea (25 g)

Compliance

FCC, CE, ISED

Contact Hexagon | NovAtel

sales.nov.ap@hexagon.com 1-800-NOVATEL (U.S. and Canada) or 403-295-4900 | China: 0086-21-68882300 | Europe: 44-1993-848-736 | SE Asia and Australia: 61-400-883-601. For the most recent details of this product: novatel.com

ALIGN, NovAtel, STEADYLINE, TerraStar and VEXXIS are trademarks of NovAtel, Inc., entities within the Hexagon Autonomy & Positioning division, their affiliated entities, and/or their licensors. All other trademarks are properties of their respective owners.

©2022 NovAtel Inc. All rights reserved. NovAtel is part of Hexagon. All trademarks or service marks used herein are property of their respective owners. NovAtel makes no representation or warranty regarding the accuracy of the information in this publication. This document gives only a general description of the product(s) or service(s) offered by NovAtel, and, except where expressly provided otherwise, shall not form part of any contract. Such information, the products and conditions of supply are subject to change without notice.

D20659 Version 5 | 01 September 2022 | Printed in Canada