

Receivers OEM7600™



COMPACT, MULTI-FREQUENCY GNSS RECEIVER DELIVERS ROBUST POSITIONING



HIGH PRECISION GNSS, COMPACT SIZE

The multi-frequency OEM7600 offers future ready precise positioning for space constrained applications with an extremely small form factor. Advanced interference mitigation features maintain high performance in challenging environments. With a variety of interface options to facilitate system integration, the OEM7600 provides the most efficient way to bring powerful Global Navigation Satellite System (GNSS) capable products to market quickly. With centimeter level positioning utilizing TerraStar® satellite-delivered correction services, the OEM7600 ensures globally available, high performance positioning without the need for expensive network infrastructure. Anywhere. Anytime.

BUILT-IN FLEXIBILITY

NovAtel®'s OEM7® firmware gives users the flexibility to configure the OEM7600 for their unique application needs. The OEM7600 is scalable to offer sub-meter to centimeter level positioning, and is field upgradeable to all OEM7 family software options. These options include ALIGN® for precise heading and relative positioning, GLIDE® for decimeter level pass-to-pass accuracy and SPAN® GNSS+INS for continuous 3D position, velocity and attitude. NovAtel CORRECT® with RTK delivers centimeter level real-time positioning, or go base-free for centimeter and decimeter PPP solutions using TerraStar corrections.

To learn more about how our firmware solutions can enhance your positioning, please visit www.novatel.com/products/firmware-options.

DESIGNED WITH THE FUTURE IN MIND

The OEM7600 features configurable channels to optimize satellite availability in any condition, no matter how challenging. It tracks current and upcoming GNSS constellations and satellite signals including GPS, GLONASS, Galileo, BeiDou, NavIC and QZSS. The OEM7600 is software upgradeable to track future signals as they become available.

FEATURES

- + 555 channel all-constellation, multi-frequency positioning solution
- + TerraStar correction services supported over multi-channel L-Band and IP connections
- + Serial, USB, CAN and Ethernet connectivity with Web interface
- + Advanced interference detection and mitigation features
- + RTK, GLIDE and STEADYLINE® firmware options
- + Simple to integrate, compact form factor with 20 g vibration performance rating
- + SPAN GNSS+INS functionality

If you require more information about our receivers, visit novatel.com/oem7

OEM7600



PERFORMANCE¹

Channel Count

555 Channels

Signal Tracking²

GPS L1 C/A, L1C, L2C, L2P, L5

GLONASS³ L1 C/A, L2 C/A, L2P, L3, L5

Galileo⁴ E1, E5 AltBOC, E5a, E5b

BeiDou B1I, B1C, B2I, B2a

NavIC (IRNSS) L5

SBAS L1, L5

QZSS L1 C/A, L1C, L2C, L5

L-Band up to 5 channels

Horizontal Position Accuracy (RMS)

Single Point L1 1.5 m

Single Point L1/L2 1.2 m

SBAS⁵ 60 cm

DGPS 40 cm

TerraStar-L™⁶ 40 cm

TerraStar-C PRO™⁶ 2.5 cm

TerraStar-X™⁶ 2 cm

RTK 1 cm + 1 ppm

Initialization time < 10 s

Initialization reliability >99.9%

Maximum Data Rate

Measurements up to 100 Hz

Position up to 100 Hz

Time to First Fix

Cold start⁷ < 39 s (typical)

Hot start⁸ < 20 s (typical)

Signal reacquisition

L1 < 0.5 s (typical)

L2 < 1.0 s (typical)

Time Accuracy⁹ 20 ns RMS

Velocity Accuracy

< 0.03 m/s RMS

Velocity Limit¹⁰ 515 m/s

PHYSICAL AND ELECTRICAL

Dimensions 35 × 55 × 13 mm

Weight 31 g

Power

Input voltage +3.3 VDC ±5%

Power Consumption¹¹

GPS L1 0.9 W (typical)

GPS/GLONASS L1/L2 1.3 W (typical)

All frequencies/All constellations with L-Band 1.8 W (typical)

Antenna Port Power Output

Output voltage 3.3 VDC ±5%

Maximum current 100 mA

Connectors

Main

60-pin dual row female socket

Antenna Input

RA MMCX female

COMMUNICATION PORTS

5 LVCMOS Serial up to 460,800 bps

2 CAN Bus 1 Mbps

1 USB 2.0 (device) HS

1 USB 2.0 (host) HS

1 Ethernet 10/100 Mbps

ENVIRONMENTAL

Temperature

Operating -40°C to +85°C

Storage -55°C to +95°C

Humidity 95% non-condensing

Vibration

Random MIL-STD 810G (CH1)

Method 514.7

(Cat 24, 20 g RMS)

Sinusoidal IEC 60068-2-6

Bump ISO 9022-31-06 (25 g)

Shock

Operating

MIL-STD-810G (CH1),

Method 516.7 (40 g)

Non-operating

MIL-STD-810G (CH1),

Method 516.7 (75 g) Survival

Acceleration

Operating

MIL-STD 810G (CH1),

Method 513.7 (16 g)

COMPLIANCE

FCC, ISED, CE and

Global Type Approvals

FEATURES

- Field upgradeable software
- Differential GNSS positioning
- Differential correction support for RTCM 2.1, 2.3, 3.0, 3.1, 3.2, 3.3, 3.4, CMR, CMR+, RTCA and NOVATELX
- Navigation output support for NMEA 0183 and detailed NovAtel ASCII and binary logs
- Receiver Autonomous Integrity Monitoring (RAIM)
- GLIDE and STEADYLINE smoothing algorithms
- Interference Toolkit
- Web GUI
- Outputs to drive external LEDs
- 4 Event inputs
- 4 Event outputs
- Pulse Per Second (PPS) output

FIRMWARE SOLUTIONS

- ALIGN
- SPAN
- RTK
- RTK ASSIST™
- TerraStar PPP
- API

OPTIONAL ACCESSORIES

- VEXXIS® GNSS-500 and GNSS-800 series antennas
- Compact GNSS antennas
- OEM7 Development Kit

For the most recent details of this product: novatel.com/oem7

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada) or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia

61-400-883-601

Version 6

Specifications subject to change without notice ©2019 NovAtel Inc. All rights reserved.

NovAtel, OEM7, SPAN, NovAtel CORRECT, VEXXIS, ALIGN, GLIDE, STEADYLINE, OEM7600 and RTK ASSIST are trademarks of Novatel Inc.

All other trademarks or service marks used herein are property of their respective owners.

Printed in Canada.

D21051 November 2019



¹ Typical values. Performance specifications subject to GNSS system characteristics, Signal-In-Space (SIS) operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

² Model-configurable to track L5/E5a (all / Galileo) through L2 (GPS) or L3/E5b/B2 (GLONASS / Galileo / BeiDou) through L2 (GLONASS). See manual for details.

³ Hardware ready for L3 and L5.

⁴ E1bc support only.

⁵ GPS only.

⁶ Requires subscription to TerraStar data service. Subscriptions available from NovAtel.

⁷ Typical value. No almanac or ephemerides and no approximate position or time.

⁸ Typical value. Almanac and recent ephemerides saved and approximate position and time entered.

⁹ Time accuracy does not include biases due to RF or antenna delay.

¹⁰ Export licensing restricts operation to a maximum of 515 meters per second, message output impacted above 500 m/s.

¹¹ Typical values using serial port communication without interference mitigation and Ethernet disabled. Consult the OEM7 User Documentation for power supply considerations.