

DUAL-FREQUENCY SMART ANTENNA FEATURING POWERFUL OEM6® TECHNOLOGY



SCALABLE PERFORMANCE

From single-frequency GLIDE™ autonomous tracking to dual-frequency Real Time Kinematic (RTK), the SMART6 positions you for success. The SMART6 integrates NovAtel's OEM6 receiver and Pinwheel® antenna technologies in a single, rugged housing. Software upgradable, the SMART6 eliminates the need for costly hardware replacement as requirements change, while delivering scalable accuracy and performance.

MULTI-CONSTELLATION FOR ENHANCED POSITIONING

Capable of tracking L1/L2 GPS+GLONASS, the SMART6 improves position availability in obstructed sky conditions. Dual-frequency tracking minimizes the impact of ionospheric disturbances, further enhancing field productivity.

SMOOTH PASS-TO-PASS ACCURACY USING GLIDE

SMART6 features NovAtel's GLIDE technology, providing ultra-smooth positioning and exceptional pass-to-pass accuracy. GLIDE's steady, smooth output is especially well suited for manual guidance and autosteer applications and will bridge through short periods of poor satellite availability. Dual-frequency GLIDE further improves the absolute accuracy of the GLIDE position and creates a robust solution, resistant to the effects of high ionospheric activity.

TILT COMPENSATION FOR INCREASED ACCURACY

With optional integrated tilt compensation, the SMART6 improves guidance and autosteer performance on uneven terrain.

INTEGRATED BLUETOOTH® CONNECTIVITY

SMART6 is available with optional Bluetooth technology to provide wireless connectivity.

MULTIPLE INTERFACES FOR MAXIMUM FLEXIBILITY

NMEA 0183 compatible RS-232 serial ports, a NMEA2000 compatible CAN port and Bluetooth wireless technology provide maximum flexibility. The SMART6 also provides simulated radar ground speed output, 1 PPS output, an event mark input and three daylight readable status LEDs. Built-in magnets simplify mounting. Fixed mounting options are also available.

BENEFITS

- + Dual-frequency capable for enhanced accuracy, reliable positioning and ionospheric disturbance mitigation
- + Flexible accuracy from entry level L1 to centimetre level RTK positioning with NovAtel CORRECT™
- + Increased position availability with GLONASS tracking
- + Smooth, consistent positions for pass-to-pass applications with GLIDE technology

FEATURES

- + 120 channels
- + GPS, GLONASS, BeiDou, Galileo and SBAS tracking
- + Optional Bluetooth
- + Optional tilt compensation
- + Simulated radar ground speed output
- + Proven NovAtel Pinwheel antenna technology inside

For more information about our SMART antenna products, visit www.novatel.com/smart-antennas

SMART6™

PERFORMANCE¹

Channel Configuration

120 channels²

Signal Tracking

GPS	L1, L2, L2C
GLONASS	L1, L2
Galileo	E1
BeiDou	B1
SBAS ³	

Horizontal Position Accuracy (RMS)

Single Point L1	1.5 m
Single Point L1/L2	1.2 m
NovAtel CORRECT™	
» SBAS	0.6 m
» DGPS	0.4 m
» RTK	1 cm + 1 ppm

Measurement Precision (RMS)

Fully independent code and carrier measurements

	GPS	GLO
L1 C/A codes	4 cm	15 cm
L1 carrier phase	0.5 mm	1.5 mm
L2 P(Y) code ⁴	8 cm	8 cm
L2 carrier phase ⁴	1.0 mm	1.5 mm
L2C code ⁵	8 cm	8 cm
L2C carrier phase ⁵	1.0 mm	1.5 mm

Maximum Data Rate⁶

Measurements	Up to 20 Hz
Position	Up to 20 Hz

Time to First Fix

Cold Start ⁷	<50 s (typical)
Hot Start ⁸	<35 s (typical)

Signal Reacquisition

L1	0.5 s (typical)
L2	<1.0 s (typical)

Velocity Accuracy⁹ 0.03 m/s RMS

Time Accuracy¹⁰ 20 ns RMS

PHYSICAL AND ELECTRICAL

Dimensions

155 mm diameter × 81 mm height

Weight <520 g

Connector 14-pin Tyco Ampseal

Mounting

2 × magnetic mount

4 × M4 screw inserts

Optional mounting plate

Optional pole-mount adapter plate

Power

Input Voltage Range	+8 to +36 VDC
Power Consumption	3.5 W (typical) ¹¹

Status LEDs

Power	
Position Valid	
Enhanced Accuracy	

I/O Protection	ISO 7637
	ISO 15003

Emissions and Immunity

ISO 14982: EMC for Agricultural machinery

ENVIRONMENTAL

Temperature

Operating	-40 to +70°C
Storage	-55 to +90°C

Humidity MIL-STD-810G Method 507.5

Immersion MIL-STD-810G Method 512.5

Shock MIL-STD-810G Method 516.6

Solar Radiation EN60950-22 8.2

MIL-STD-810G Method 505.5

Salt Fog MIL-STD-810G Method 509.5

Sand and Dust MIL-STD-810G Method 510.5

Vibration

Random MIL-STD-810G, Method 514.6E-1
Sinusoidal ASAE EP455, 5.15.2 Level 1 & 2

Compliance FCC, IC, CE marking

Ingress Protection Rating IP67

COMMUNICATION PORTS

3 RS-232 serial ports

1 CAN Bus NMEA2000

1 Bluetooth (optional)¹²

1 PPS

1 Ground Speed Output

1 Event Mark Input

STANDARD FEATURES

- GPS L1 position, velocity and time with SBAS support
- 20 Hz data rates
- Field upgradable software
- PAC multipath mitigating technology
- Differential correction support for RTCM 2.1, 2.3, 3.0, 3.1, CMR, CMR+ and RTCA
- Navigation output support for NMEA 0183 and detailed NovAtel ASCII and binary logs

- GLIDE smoothing algorithm
- Emulated radar

HARDWARE OPTIONS

- Tilt hardware (optional)
- Bluetooth wireless technology (optional)

FIRMWARE OPTIONS

- Dual-frequency tracking
- GLONASS tracking
- Galileo tracking
- BeiDou tracking
- ALIGN®
- RAIM

OPTIONAL ACCESSORIES

- Mounting plate
- Pole-mount adapter plate
- Interface cable

For the most recent details of this product:

www.novatel.com/products/smart-antennas/smart-6/

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)
or 403-295-4900

China 0086-21-68882300

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

Version 5 Specifications subject to change without notice.

©2015 NovAtel Inc. All rights reserved.

OEM6, NovAtel, Pinwheel and ALIGN are registered trademarks of NovAtel Inc.

SMART6, GLIDE and NovAtel CORRECT are trademarks of NovAtel Inc.

Any use of such marks by NovAtel Inc. is under license. Other trademarks and trade names are those of their respective owners.

D18373 November 2015

Printed in Canada



1. Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

2. Tracks up to 60 L1/L2 satellites.

3. GPS only.

4. L2 P for GLONASS.

5. L2 C/A for GLONASS.

6. 20 Hz while tracking up to 20 satellites.

7. Typical value. No almanac or ephemerides and no approximate position or time.

8. Typical value. Almanac and recent ephemerides saved and approximate position and time entered.

9. Export licensing restricts operation to a maximum of 515 metres per second.

10. Time accuracy does not include biases due to RF or antenna delay.

11. Power consumption values for GPS L1/L2.

12. Optional Bluetooth connectivity reduces the number of RS-232 serial ports to two. Non-Bluetooth models have three RS-232 serial ports.

